

SANTAK® CASTLE SERIES ON-LINE UPS

# CASTLE 3C3 PRO

20-200kVA



# Crucial moment, Powering your business

## SANTAK UPS PROVIDE RELIABLE PROTECTION FOR CRITICAL EQUIPMENT AND DATA

- Higher power density, more power output
- Wider input range, higher efficiency
- Ultra low noise, multiple configurable options
- High quality LCD with wide view

#### TYPICAL APPLICATION

- Small, Medium Data Center
- Computer Room
- Telecom
- Automation Control System
- Security and Surveillance System
- CCTV System
- Production Process Control
- Petro Chemical Industry







Power Rating: 20/30/40/60/80/100/120/160/200kVA

**Topology:** Double conversion topology on-line UPS High frequency IGBT Tower design

Input & Output: 220V/380V 4-Wire

Frequency: 50/60 Hz

### **Key Feature:**

- 0.9 output factor
- Parallel up to 4 units
- Intelligent battery performance management
- ECO mode
- Battery quantity adjustable
- Easy installation and maintenance

3C3 PR	O MODEL	W (mm)	D (mm)	H (mm)	S (m²)	
20	KVA					
30	KVA	420	715	900	0.30	
40	KVA					
60	KVA	600	720	1200	0.43	
80	KVA	800	720	1200	0.43	
100	OKVA	600	800	1876	0.48	
120	KVA	000	800	1070	0.40	
160	OKVA	600	830	1876	0.50	
200	OKVA	000	630	1076		

#### ENHANCE ENVIRONMEN-TAL ADAPTABILITY

#### **Anti-Corrosion Production**

PCBA corrosion is one of the key reasons leading to UPS components failure, especially in coastal areas. SANTAK applies advanced PCBA coating technology, offering customers an excellent anti-corrosion performance.

#### **Optimized Programming**

According to the system
design and air distribution,
we directly program on the
equipment to achieve on demand spraying, meanwhile
considering the possible salt
spray and dust accumulation
probability.

#### **Automatic Coating Process**


 Automatic coating technology adopted, the coating precision and consistency is highly improved, comparing with manual coating technology.

#### **Blue-ray Detection**

Assisted with blue-ray detection technology, PCBA coating quality is significantly improved.



PCBA before Coating



PCBA after Coating

#### **Dustproof Design**


3C3 PRO offers standard air filter kits, which prevent the dust out of the UPS and improves the environmental adaptability. The filtration kit meets with

- Easy disassemble and clean, low maintenance cost;
- Flame resistant:

In additional, the internal design of 3C3 PRO optimizes the internal air flow distribution, which significantly decreases the dust deposition.


## LEADING PARALLEL TECHNOLOGY

3C3 PRO is embedded with internal parallel kits powering by high reliability CAN bus. With better output voltage regulation, perfect load sharing and active protection, 3C3 PRO assure the reliability and redundancy of the paralleling power system. 3C3 PRO offers more excellent performance in paralleling and improves the output accuracy.



#### SANTAK INTELLIGENT BATTERY MANAGEMENT TECH-NOLOGY

3C3 PRO adopts the advanced 3-stage charging technology. In the first stage, it charges the battery up to 90% capacity with high current. In the second stage, it charges the battery to 100% capacity with constant voltage. In the third stage, it stays in rest mode. The 3-stage charging method can extend the battery life cycle avoiding long-time floating charge issues. SANTAK intelligent battery management technology can accurately forecast battery working mode and remind your customers of potential malfunction.



3C3 PRO supports flexible battery quantity configuration. Customers possess flexibility to choose different battery capacity and quantity in the backup solution. Even in the on-run mode, the battery quantity configuration can be quickly adjusted to disassemble the malfunctioning battery, while the whole UPS system can guarantee a constant power supply.

## STK CASTLE BATTERIES

#### ----Maintenance-free Sealed Lead-acid UPS Batteries

CASTLE C12V series batteries are being designed with more focusing on compatibility with SANTAK UPS and system. Compare to other batteries in the market, CASTLE C12V series batteries can provide longer float charging life time and more powerful discharging characteristics. It is an ideal product for SANTAK UPS backup application.



# 3C3 PRO 20-200kVA Product Specification

Model		3C3 Pro- 20KS	3C3 Pro- 30KS	3C3 Pro- 40KS	3C3 Pro- 60KS	3C3 Pro- 80KS	3C3 Pro- 100KS	3C3 Pro- 120KS	3C3 Pro- 160KS	3C3 Pro- 200KS		
Power	kVA	20	30	40	60	80	100	120	160	200		
rating	kW	18	27	36	54	72	90	108	144	180		
Topology		Double co	nversion, IGBT	based								
UPS rectifi	er/input											
Topology		PWM, IGB	PWM, IGBT based									
Rated voltage		380Vac/220Vac										
Voltage range		-50%-20%, depends on load percentage										
Input powe	er factor	0.99										
THD (i)		<5%										
Rated frequ	uency	50/60Hz au	uto sensing									
Frequency	range	42-72 Hz										
UPS Outpu	ıt											
Power facto	or	0.9	0.9									
Efficiency		Up to 94%	Up to 94% in online mode; >98% in ECO mode									
Output vol	tage	380Vac/22	0Vac +/-1%									
Overload ca	apacity	<105% conf	tinuous run; 10	05%-125% 10n	nin							
THDV		<2% for Lin	<2% for Linear load									
Output free	quency	50/60Hz	50/60Hz									
Unbalance	d load	1										
Crest facto	r	3:1	3:1									
Bypass												
Maintenan	ce bypass	Standard Optional NA										
Bypass volt	tage	380Vac (+/-15%)										
Internal sta	atic switch	Standard										
Battery												
Battery typ	е	VRLA										
Backup tim	ne	Varies from battery capacity and load situation										
Battery PC	S	28-36 PCS	28-36 PCS adjustable, 32PCS default					36-40 PCS adjustable, 40PCS default				
Recharge t	ime	8 hour to 9	90%					-				
Communic												
Interface		RS232, Min	ni slot									
Accessories	s (optional)	SNMP/WEB, Modbus/Ethernet, AS400, NMC										
	nvironment											
Running te	mperature	0~40°C										
Storage		-25~55°C										
Humidity		5%~95%										
Elevation		No derating < 1000m										
Certificatio	ons											
EMC		IEC61000-4	4									
EMI		EN5550022/EN55024										
Quality		ISO90001: 2000, ISO14001: 1996										
	43fication	CE										







### SANTAK ELECTRONIC (SHENZHEN) CO., LTD.

Shenzhen, P.R. China Address: No. 8 Baoshi Road, Baoan Fax: 0086 755 27572730 (27572480) District, Shenzhen, 518101

Tel: 0086 755 27572666 Email: santakexport@santak.com Website: www.santak.com

October. 2023 EN-00005-01